



# HAIR DRYER

## ALTEO PLUG



### PRODUCT + 'S



Patented LighTouch® handle which switches on by simply picking it up



1875 W power



6 drying settings and fitted with an ionizing system



Integrated concentrator nozzle



REF 8 22 1044  
Alteo Black 1875  
W + socket



REF 8 22 1139  
Alteo Chrome 1875  
W + socket



REF 8 22 1140  
Alteo Matte Black  
1875 W + socket



REF 8 22 1043  
Alteo White 1875 W  
+ socket

*Alteo hair dryer with plug equipped with patented LighTouch handle and 6 drying settings. JVD exclusif design. 2-year warranty.*

DESIGNED IN FRANCE



# HAND DRYER

## ALTEO PLUG



### ELECTRICITY

Power supply	230 V
Power supply	50/60 Hz
Rated power	1875 W
Electrical insulation	Classe II
IP index	21
Electrical safety in case of malfunction	Yes

### PERFORMANCE

LighTouch handle	Yes
Drying settings	6
Flow rate	70 - 115 m <sup>3</sup> /h
Temperature settings	3
Ionizing system	Yes
Integrated concentrator nozzle	Yes
Sound level at 1m - Position 1 (70 m <sup>3</sup> /h)	70 dB
Sound level at 1m - Position 2 (115 m <sup>3</sup> /h)	77 dB
Removable back filter	Yes

### LOGISTICS

Net weight	0.650 kg
Gross weight	0.860 kg
Logistics unit	12
HS code	8516310000
Gencod - Alteo black	3324120010440
Gencod - Alteo chrome	3324120011393
Gencod - Alteo matte black	3324120011409
Gencod - Alteo white	3324120010433

### DIMENSIONS

- Dim. : 245 (L) x 205 (H) x 84 (D) mm
- Cable (folded / unfolded): 700 / 2050 mm

### POWERS

Tests carried out at 1m in front of the device

	Flow rate Position 1 70 m <sup>3</sup> /h	Flow rate Position 2 115 m <sup>3</sup> /h
Temperature COOL	235 W	410 W
Temperature Niveau I	560 W	1100 W
Temperature Niveau II	900 W	1875 W

### INSTALLATION

Can be installed in volume area 2 if the cable is not locked in place by a support.

