



8111790RBN-A

Hand Dryer – Copt’Air Stainless Steel

This refurbished Copt’Air hand dryer in stainless steel is an air-pulsed model with a stainless steel cover, ideal for restrooms with frequent use. It features touchless automatic activation, an optional antibacterial filter, and a moderate sound level. Refurbished in our workshops in partnership with the ESAT of Rezé, it comes with a 2-year warranty.



PRODUCT PLUSES

- 100% new drying sensations with a cyclonic effect
- 65% more economical than competitors' models
- 100% Anti-vandalism: stainless steel cover


ECO-FRIENDLY

- Refurbished in France as part of the Reborn project
- Reduces electronic waste and extends product lifespan
- Inclusive manufacturing in partnership with the ESAT of Rezé



REPAIRABLE 10 YEARS

MADE IN FRANCE



8111790RBN-A

Hand Dryer – Copt’Air Stainless Steel Refurbished

Version	17/03/2026
---------	------------

Color	Stainless steel
Drying time (s)	10-15s
Sound level (dB) (1m in front of the appliance)	80
Air outlet speed (m/s)	90
Air flow rate (m³/h)	130
Air outlet temperature (°C)	40
Safety in case of malfunction	Yes
Filter	Anti-bacterial filter (Option)
Anti-vandalism	Yes
Lighting of the drying area	Yes
Triggering	Automatic via infrared

Power consumption during operation (W)	600
Power supply	220-240V
Frequency (Hz)	50
Standby power (W)	2.2
Motor rotation speed (rpm)	24000
Motor type	Brushed AC
Motor lifespan (number of cycles)	350000
IP rating	24
IK rating	IK10
Electrical insulation	Class II
Installation volume	Volume 2

Product height (mm)	285
Product width (mm)	232
Product depth (mm)	196
Net Weight (kg)	5.05

Package height (mm)	205
Package width (mm)	295
Package depth (mm)	240
Gross Weight (kg)	5.36

Material	Stainless Steel (1718g), Recycled ABS (1103.5g), Plastic (350g), AIR Motor (1485g), Other (455.7g) (0.5g)
----------	---

<ul style="list-style-type: none"> • Installation height for men (cm) : 130 • Installation height for women (cm) : 120 	Recycled Cardboard (213g) Paper (94.8g)
--	--

- Installation height for children (cm) : 120
- Installation height for PMR (cm) : 100

TECHNICAL DRAWING

